

◀ SD 4010 ▶



【Product name】 DC Brushless Motor 410

【Model】 SD 4010

【Size】 40 x 40 x 10 mm

【Frame】 Plastic Material UL94V-0

【Impeller】 Plastic Material UL94V-0

【Speed Range】 ±10%

【Operating Temperature】

Ball Bearing -20°C to + 70°C

Sleeve Bearing -10°C to + 65°C

Specifications

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (mH2O)	Speed (R.P.M)	Rated Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)		
SD-4010C5H	Two Ball	5	4.25~5.75	6.20	3.21	6000	0.16	0.8	28.6	17		
SD-4010C5M				5.56	2.75	5400	0.10	0.5	26.5			
SD-4010C5L				4.25	1.79	4200	0.08	0.4	21.6			
SD-4010B5H	Ball + Sleeve			6.20	3.21	6000	0.18	0.9	28.6			
SD-4010B5M				5.56	2.75	5400	0.12	0.6	26.5			
SD-4010B5L				4.25	1.79	4200	0.08	0.4	21.6			
SD-4010S5H	Sleeve			6.20	3.21	6000	0.24	1.2	28.6			
SD-4010S5M				5.56	2.75	5400	0.16	0.8	26.5			
SD-4010S5L				4.25	1.79	4200	0.12	0.6	21.6			
SD-4010C1H	Two Ball			12	10.2~138	6.20	3.21	6000	0.07		0.8	28.6
SD-4010C1M						5.56	2.75	5400	0.06		0.7	26.5
SD-4010C1L						4.25	1.79	4200	0.05		0.6	21.6
SD-4010C1H	Ball + Sleeve	6.20	3.21			6000	0.09	1.1	28.6			
SD-4010C1M		5.56	2.75			5400	0.06	0.7	26.5			
SD-4010C1L		4.25	1.79			4200	0.05	0.6	21.6			
SD-4010B1H	Sleeve	6.20	3.21			6000	0.10	1.2	28.6			
SD-4010B1M		5.56	2.75			5400	0.07	0.8	26.5			
SD-4010B1L		4.25	1.79			4200	0.06	0.7	21.6			

Specification subject to change without notice

