

**SD 6010**



**【Product name】** DC Brushless Motor 610

**【Model】** SD 6010

**【Size】** 60 x 60 x 10 mm

**【Frame】** Plastic Material UL94V-0

**【Impeller】** Plastic Material UL94V-0

**【Speed Range】** ±10%

**【Operating Temperature】**

Ball Bearing                      -20°C to + 70°C  
Sleeve Bearing                    -10°C to + 65°C

**Specifications**

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (mH2O)	Speed (R.P.M)	Rated Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)
SD-6010C1H	Two Ball	12	10.2~13.8	21.80	3.92	5000	0.23	2.8	37.6	27.0
SD-6010C1M				18.10	2.78	4200	0.17	2.1	32.9	
SD-6010C1L				14.96	1.95	3500	0.13	1.6	28.1	
SD-6010B1H	Ball + Sleeve			21.80	3.92	5000	0.23	2.8	37.6	
SD-6010B1M				18.10	2.78	4200	0.17	2.1	32.9	
SD-6010B1L				14.96	1.95	3500	0.13	1.6	28.1	
SD-6010S1H	Sleeve			21.80	3.92	5000	0.23	2.8	37.6	
SD-6010S1M				18.10	2.78	4200	0.17	2.1	32.9	
SD-6010S1L				14.96	1.95	3500	0.13	1.6	28.1	

Specification subject to change without notice

