

SD 6020



【Product name】 DC Brushless Motor 620

【Model】 SD 6020

【Size】 60 x 60 x 20 mm

【Frame】 Plastic Material UL94V-0

【Impeller】 Plastic Material UL94V-0

【Speed Range】 ±10%

【Operating Temperature】

- Ball Bearing -20°C to + 70°C
- Sleeve Bearing -10°C to + 65°C

Specifications

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (mH2O)	Speed (R.P.M)	Rated Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)
SD-6020	Two Ball Ball + Sleeve Sleeve	12	10.2~13.8	19.11	7.38	5500	0.21	2.52	35.9	50.0
SD-6020				17.41	6.27	5000	0.19	2.28	32.8	
SD-6020				15.56	4.97	4500	0.17	2.04	29.4	
SD-6020				13.84	3.99	4000	0.15	1.80	26.4	
SD-6020				12.06	3.23	3500	0.13	1.56	23.6	
SD-6020				10.13	2.28	3000	0.10	1.20	20.3	
SD-6020				8.48	1.72	2500	0.08	0.84	17.0	
SD-6020	Two Ball Ball + Sleeve Sleeve	24	20.4~27.6	19.11	7.38	5500	0.17	4.08	35.9	
SD-6020				17.41	6.27	5000	0.15	3.60	32.8	
SD-6020				15.56	4.97	4500	0.13	3.12	29.4	
SD-6020				13.84	3.99	4000	0.11	2.64	26.4	
SD-6020				12.06	3.23	3500	0.09	2.16	23.6	
SD-6020				10.13	2.28	3000	0.07	1.68	20.3	
SD-6020				8.48	1.72	2500	0.05	1.20	17.0	

Specification subject to change without notice

